


The **BTH-300-MAX** is a Broadly Compatible, Wireless Lapel Microphone Kit designed for use with:

- \* PRYMEBLU Wireless adapters
- \* Kenwood, Icom, EF Johnson, and Bendix King two-way radios with onboard Bluetooth technology
- \* Apple and Android phones running Zello or ES Chat PoC (PTT Over Cellular) apps. 

**MSRP Starting at \$115**

**BASE UNIT ONLY - EARPIECE KITS ADDITIONAL**  
(Wall charger included)

## FEATURES

- 10+ hours of battery life
- Built-in wireless PTT
- Inconspicuous status LED
- Available with one of seven different earpiece accessories. Also compatible with Apple-compatible earbuds and audio accessories, either with or without a microphone.
- Built-in microphone (for earphone-only applications) with auto-switch technology. Automatically selects the external microphone if one is plugged in, or the internal mic if listen-only earphones are being used.
- Adjustable volume controls that remember settings, even when unit is turned off
- 360° metal, swivel, clothing clip allows user to wear comfortably
- Micro USB charging jack


## ALTERNATE VERSIONS AVAILABLE

While the BT-300-MAX is broadly compatible with a wide-variety of devices, some radios or PoC apps may require one of these alternate versions instead:

- BTH-300-HA** For Harris radios with onboard Bluetooth technology
- BTH-300-HY** For Hytera radios with onboard Bluetooth technology
- BTH-300-KU** For Motorola Wave PTT and Kodiak PTT compatible PoC apps



You can use the Base Unit with your own Apple® compatible headset (not included.)  
**OR add one of these 7 unique PRYME accessories:**



SPECIFICATIONS	
Type:	Wireless Lapel Microphone
Operating Temp:	-10°C ± 2°C ~ 50°C ± 2°C
Approx. Weight:	21.6g (Excluding earphone)
Size:	65mm X 30mm X 12mm
<ul style="list-style-type: none"> <li>• Fully Qualified BT v5.0</li> <li>• Support AES-128 and ECC-256</li> <li>• Echo cancellation, noise reduction and extended features</li> <li>• High Quality DAC</li> <li>• 80MHz RISC MCU and 80MIPS Kalimba DSP</li> <li>• SBC, MP3, AAC, Fast stream, APTX codec support</li> <li>• RoHS compliant</li> <li>• HSP, HFP, A2DP, AVRCP profile supports</li> </ul>	
PTT function:	built-in
Talking Range:	BT class 2, 10 meters
Display LED:	Blue and Red
Power:	Max 4dB
Sensitivity:	-90dB
DC Input:	5 Vdc (std.)
Standby Current:	6mA
Battery:	190mAh Lithium-Ion
Standby Time:	50 hours
Talk Time:	10 Hours typical
Continuous Talk Time	> 5 Hours