

PRYME® HBB-EM SERIES High Performance Dual Muff Headsets

The HBB-EM Series is a professional grade, dual-muff headset perfect for racing intercom, avionics, and industrial use. Receive audio is heard over loud dual-muff earphones and the adjustable boom microphone ensures clear audio on transmit. The HBB-EM Series is lightweight, comfortable and easy to adjust to fit any user.

MSRP \$229 + cable

Depending on connector; see pages 76-82

Certified NRR 24dB ANSI S3.19-1974



**MODEL NUMBER:
HBB-EM-OHB (Black)**
Over-the-Head



More than 35 different radio cables available. 2-Pin Aviation cable also available. Page 58

NEW: CABLES FOR CELLULAR PHONES



- Easy-to-replace Microphone
- Noise canceling Electret (Optional Dynamic)

FEATURES

- Dual muff style headset with padded, adjustable Head Band
- Lightweight, comfortable, and easy to adjust
- Super Comfort Foam Ear Pads or Optional GEL filled Ear Pads
- Aviation-style boom microphone with flexible arm
- Optional Noise-canceling microphone reduces transmitted background noise
- Removable and replaceable radio interface cable (Optional Tactical Kit available)
- Loud muff earphones allow the user to hear incoming signals easily
- Tactile PTT button mounted in the right earphone
- Replaceable microphone
- Volume control rotary
- 5P Mini XLR Connector

REPLACEMENT PARTS		
P-EM-EMIC	Standard Electret Mic	Included
P-EM-DMIC	Dynamic Microphone	\$25
P-EM-CLOTHC	Soft Cloth Earpad Covers - pair	\$5/pair
P-EM-FOAMPADS	Replacement Foam Filled Earpads - pair	\$10/pair
P-EM-GELPADS	Replacement Gel-Filled Earpads - pair	\$45/pair
P-EM-HYGCOVERS	Replacement DISPOSABLE Earpad Covers - pair	\$2/pair
P-EM-MSOCK	Replacement Mic Wind Sock and Band	\$2

SPECIFICATIONS	
MICROPHONE	
Type	Noise Canceling Condenser Mic
Sensitivity	-47±-3dB (at L=50mm)
Impedance	Low Impedance 680Ω
Frequency	300Hz~10KHz
Standard operation voltage	1.0V
Sensitivity reduction	Within -3dB at 1V
S/N ratio	More than 60dB
SPEAKER	
Size	50mm
Impedance	300 Ohm ±- 1% @ 1kHz
Power Rating	30mW RMS
Output Sound Pressure Level	95 ± 3dB / 1100mW
Frequency Range	100Hz~3,000Hz
PHYSICAL	
Color	Black
Plug	5P Mini Chassis XLR Connector, Male
Ear Pads	Flexible inert foam
PTT Switch	500,000 cycle rated