

The **BTH-600-MAX** is a Broadly Compatible, Heavy Duty, Wireless Remote Speaker Microphone designed for use with:

- PRYMEBLU Wireless adapters
- Kenwood, Icom, EF Johnson, and Bendix King two-way radios with onboard Bluetooth technology\* Apple and Android phones running Zello or ES Chat PoC (PTT Over Cellular) apps. 



The BTH-600-MAX is the more powerful, heavy-duty Wireless RSM requested by our customers. Based on the SPM-4200 StormTrooper® series, the BTH-600-MAX is water and dust resistant, and has incredible battery life.

**FEATURES**

- Wireless version of StormTrooper®
- Noise reduction microphone element
- Push button volume controls (UP and DOWN)
- Powered by a removable/replaceable BL-5C Nokia cell phone battery (included) which provides up to 40-hours of operation and 30-days of standby on a single charge.
- Includes mini USB charging cable and universal wall charger
- Operating range of up to 10-meters (30-feet)
- Built-in wireless PTT
- Built-in earphone jack for additional privacy and security. Compatible with a standard 3.5 mm earphone plug such as our LOOKOUT™, RECON™ or SCOUT™ (sold separately - see pg 12)

**ALTERNATE VERSIONS AVAILABLE**

While the BTH-600-MAX is broadly compatible with a wide-variety of devices, some radios or PoC apps may require one of these alternate versions instead:

- BTH-600-HA** For Harris radios with onboard Bluetooth technology
- BTH-600-HY** For Hytera radios with onboard Bluetooth technology
- BTH-600-KU** For Motorola Wave PTT and Kodiak PTT compatible PoC apps



Connects wirelessly to PRYMEBLU® radio adapters, such as the BT-523



Wall charger and cord included

**OPTIONAL EARPHONES**

Although the PRYMEBLU® Speaker Microphone has a built-in speaker for listening to received calls, some users may prefer to use a listen-only earphone for enhanced privacy. The accessory jack on the speaker microphone will accept any mono earphone with a 3.5 mm audio plug. When an earphone is used, the front-firing speaker is disabled.

MODEL	EARPHONE STYLE	CABLE LENGTH/STYLE
EH-389SC	Rubber Earhook	15" Coiled
EH-389XC	Rubber Earhook	25" Coiled
EH-1289SC	Plastic D-Ring	15" Coiled
EH-1289XC	Plastic D-Ring	25" Coiled
EH-1389SC	Acoustic Tube	15" Coiled
EH-1389X	Acoustic Tube	30" Straight
EH-1399X	Acoustic Tube	30" Straight
EH-GH89SC	G-Hook (swivel)	10" Coiled



EH-1389SC model shown. Earphone sold separately. See pg 12 for more info.

SPECIFICATIONS	
BT Version	V4.1 fully qualified
Speaker Output	2 wattw
Receiver Sensitivity	-82 dBm (typ.)
Power Class	BT class 2
Range	10 meters
Display	Blue, Red, and Green
BT Profile	HSP / HFP / A2DP / AVRCP
Operating Voltage	5 VDC
Battery Capacity	1,020 mAH
Operating Time (Standby)	> 30 days
Operating Time (Typical)	> 80 hours
Operating Time (Continuous Talk)	> 40 hours
Push-to-Talk Function	Built-in
Operating Temperature	-4°F to +120°F (approx.)